

TXAMPumps

# PTP Series

The TXAM PTP3500 & PTP6500 series pneumatic pumps are built for operating in the most corrosive of environments. Made up of 316 stainless steel, the PTP series operates off natural gas or compressed air.

Available in either 1/4", or 3/8" plungers, the built-in stroke length adjustment and pneumatic timer are also utilized to precisely control your injection rates. The stroke speed adjustments can be easily made by turning the built-in stroke adjustment knob. The turn down ratio allows for extremely low, to the highest attainable dosing. Recommended supply pressures range from 50 - 70 PSI.

*Please contact your local TXAM sales representative for more details.*

## Max Pressure: 3500 or 6500 PSI/0 to 30 GPD

- Single Injection
- Stainless Steel Pump Body
- Stainless Steel Head Assembly
- Single Rate Control Options via Timer
- Built-in Stroke Adjustment
- Non-Adjustable 2-Piece Packing

**LOW**

Cost of Ownership

**FAST**

Return On Investment

**SPECIFICATIONS:**

**PUMP**

Single Injection
Stainless Steel Pump Body
1/4" NPT Connections
1/4" @ 6500PSI; 12GPD
3/8" @ 3500PSI; 30GPD
Various Plunger Materials & Coatings
Pump Prime Feature

**MOTOR**

Natural Gas; Compressed Air
50-70 PSI Supply; Max 150 PSI
2-60 Strokes Per Minute

**TXAM CONTROLS**

TXAM Pneumatic Solenoid
Plunger Stroke Length Adjustments

